

# EURO E6

Low SAPS

5W30 – 10W40 Full Synthetic (Code: 9242/9231)



## DEFINITION

**EURO – E6** Long Drain is a fully synthetic ultra high performance heavy duty diesel engine oil. It meets and complies with the demanding requirements of Euro 4 exhaust emission legislation.

**EURO – E6** Long Drain is ideally designed for European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3 and Euro 4 Exhaust emission legislation.

**EURO – E6** Long Drain is not suitable for American diesels calling for CG-4, CH-4 ,CI-4 & CJ-4 performance levels.

**EURO – E6** Long Drain meets or exceeds the following specifications.

- \* ACEA E6 ISSUE 2
- \* ACEA E4 - 99 / Euro 4 Exhaust emission legislation
- \* ACEA E7
- \* MAN 3277
- \* MAN 3477
- \* MB 228.51
- \* MTU Type 3
- \* RVI RXD
- \* VOLVO VDS 2, VDS 3
- \* SCANIA Long Drain
- \* DAF 100,000km drain specification

## APPLICATIONS

Suitable for use where particulate exhaust filters are used (DPF -Diesel particulate filters).

Super extended drain intervals surpassing any mineral or American diesel type lubricant.

Excellent soot and sludge control resulting in cleaner engines.

Reduces fuel consumption due to superior technology.

Outstanding low temperature viscometrics for reduced wear at start up.

Low SAPS (Sulfated Ash, Phosphorous and Sulphur).

## TYPICAL MAIN CHARACTERISTICS

	5W30	10W40
Specific gravity at 15 C	0.882	0.878
Flash point, COC C	210	230
Pour point C	-40	-35
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	11.8	15.5
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	79	97
TBN, ASTM D2896, mg KOH/g	19	18
Viscosity index	189	150
Sulphated ash, %	1.05	0.71

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd

Website [www.ultralube.com.au](http://www.ultralube.com.au)

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C. Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

**PACKAGE SIZE** Bulk, 205 Litre, 20 Litre, 5 Litre.

**ULTRA LUBRICANTS**

23 Tempest Street, Gunnedah NSW 2380 PH: 61 2 6742 5333 EMAIL: [sales@ultralube.com.au](mailto:sales@ultralube.com.au) [www.ultralube.com.au](http://www.ultralube.com.au)