

# Euro C3

## Low SAPS

### 5w30 Full Synthetic (Code: 9281)



#### DEFINITION

**EURO C3** Low SAPS 5W30 is the most advanced development in lubrication chemistry and complies with the demanding requirements of Euro 4 exhaust emission legislation. **Euro C3** Low Saps 5W30 is ideally designed for European engines requiring SHPD level of performance and those which comply with Euro 1, Euro 2, Euro 3 and Euro 4 Exhaust emission legislation.

**EURO C3** Low SAPS 5W30 meets or exceeds the following specifications.

- \* ACEA C2-04 (2007) MB 229.51
- \* ACEA C3-04 (2004) VW 50200 (2005)
- \* ACEA A3/B4-04 (2004) VW 50500 (1997)
- \* ACEA A5/B5-04 (2007) VW 50101 (2005)
- \* API SM BMW LL- 04
- \* API CF Porsche

#### APPLICATIONS

**EURO C3** Low SAPS 5W30 is a full Synthetic Formulation and is suitable for use where particulate exhaust filters are used (DPF -Diesel particulate filters).

**EURO C3** Low SAPS 5W30 has excellent soot and sludge control resulting in cleaner engines and reduces fuel consumption due to superior technology.

**EURO C3** Low SAPS 5W30 has outstanding low temperature viscometrics for reduced wear at start up and is a dedicated European Formulation with Low SAPS (Sulfated Ash, Phosphorus and Sulfur).

#### TYPICAL MAIN CHARACTERISTICS

Specific gravity at 15 C	0.895
Flash point, COC C	230
Pour point C	-35
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	10.55
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	63.2
TBN, ASTM D2896, mg KOH/g	18
Viscosity index	161
Sulphated ash, %	0.71

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd  
Website [www.ultralube.com.au](http://www.ultralube.com.au)

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C .Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

**PACKAGE SIZE** Bulk, 205 Litre, 20 Litre, 5 Litre.

#### ULTRA LUBRICANTS