

EuroSyn VW

5W30 VW 504.00/507.00 (Code: 9280)



DEFINITION

EuroSyn VW 504/507 is a new Low SAPS generation oil especially developed for the Volkswagen Group of engines. It is designed to be used in all Diesel and Petrol engines, especially those respecting the Euro 4 standards for the reduction of polluting emissions.

EuroSyn VW 504/507 is a full Synthetic Formulation and is suitable for use where particulate exhaust filters are used.

EuroSyn VW 504/507 meets or exceeds the following specifications.

- * ACEA A3/B4-04 (2004)
- * ACEA C3
- * Volkswagen VW 504.00
- * Volkswagen VW 507.00
- * BMW Longlife 04
- * MB 229. 31, 229.51

APPLICATIONS

EuroSyn VW 504/507 has been developed with “Clean performance technology” reducing long term blocking of the particulate exhaust filters, thereby prolonging its life span and maintaining engine performance.

EuroSyn VW 504/507 guarantees a rapid build-up of a stable oil film at cold start, that remains stable at high operating temperatures, while friction is reduced in order to provide greater fuel economy.

EuroSyn VW 504/507 incorporates the highest level of anti wear, anti corrosion and anti foam properties available and allows extra long drain intervals (30,000 – 50,000 kms), thanks to an exceptional oxidation resistance.

EuroSyn VW 504/507 ensures a greater respect for the environment through its reduced emissions.

TYPICAL MAIN CHARACTERISTICS

Specific gravity at 15 C	0.848
Flash point, COC C	224
Pour point C	-36
Kinematic viscosity at 100 C, mm ² /s (cSt)	12.0
Kinematic viscosity at 40 C, mm ² /s (cSt)	73
TBN, ASTM D2896, mg KOH/g	5.9
Viscosity index	161
Sulphated ash, %	0.6

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd

Website www.ultralube.com.au

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C. Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

PACKAGE SIZE Bulk, 205 Litre, 20 Litre, 5 Litre.

ULTRA LUBRICANTS