

SYNGEAR LS

75W90 LS – 80W140 LS GL-5

(Code: 9410, 9420)



DEFINITION

SYNGEAR LS Synthetic gear grades are fully synthetic multigrade lubricants providing superior wear protection, high temperature stability and low excellent low temperature characteristics due to its blend of selected synthetic base and extreme pressure additives. It contains the Sturaco 7098 friction modifier for use in limited slip differentials that suffer from severe chatter.

SYNGEAR LS Synthetic gear grades are ideal for use in transaxles with combined manual gearbox and hypoid differentials and are designed to give maximum protection to gearboxes and differentials operating under the most severe conditions.

SYNGEAR LS Synthetic gear grades meet or exceed the following specifications.

- * API GL5, MT-1
- * MILITARY SPECIFICATIONS MIL-L-2105D, MIL-PRF-2105E
- * GENERAL MOTORS HN-1561, HN-2040
- * FORD MC20119 A, MC2-104
- * MACK GO-J * BORG WARNER 5M - 48

SYNGEAR LS Synthetic gear grades Should be used in manual transmissions and axle drives requiring API GL-4, GL-5 and MT-1 performance.

TYPICAL MAIN CHARACTERISTICS

Grade ISO	75W90	80W140
Viscosity Index	155	160
Viscosity @ 100 C (cSt)	17.5	36.5
Viscosity @ 40 C (cSt)	125	320

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd Website www.ultralube.com.au
All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C. Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

PACKAGE SIZE Bulk, 205 Litre, 20 Litre, 5 Litre.

ULTRA LUBRICANTS