

ULTRA ATF DEX III (3)

(Code: 3100)



DEFINITION

ULTRA ATF DEX III is transmission fluid designed for use in automatic transmissions where Dexron® III or Dexron® II fluids have been specified. This product is a high viscosity index fluid containing superior additive technology and greatly improved low temperature properties for smooth cold shifts. It is distinctly red in colour.

ULTRA ATF DEX III meets or exceeds the following specifications.

- * GENERAL MOTORS - DEXRON III
- * FORD MERCON
- * ALLISON C-4
- * CATERPILLAR TO-2
- * SPERRY VICKERS - HYDRAULIC PUMP SYSTEMS
- * DENISON - HYDRAULIC PUMP SYSTEMS
- * SUNSTRAND - HYDRAULIC PUMP SYSTEMS

APPLICATIONS

ULTRA ATF DEX III is used primarily for vehicles and machinery with automatic and torque convertor type transmissions requiring the specifications as stated above, in particular the Allison C4 specification. Ultra ATF Dexron III is suitable for most power steering fluid applications.

TYPICAL MAIN CHARACTERISTICS

Kinematic viscosity at 40 C, mm ² /s (cSt)	38
Kinematic viscosity at 100 C, mm ² /s (cSt)	7.4
Pour point deg C	-42
Viscosity index	160
Colour	RED

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd

Website www.ultralube.com.au

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C. Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

PACKAGE SIZE Bulk, 205 Litre, 20 Litre, 5 Litre, 1 Litre

ULTRA LUBRICANTS

23 Tempest Street, Gunnedah NSW 2380 PH: 61 2 6742 5333 EMAIL: sales@ultralube.com.au www.ultralube.com.au