

ULTRATEC SUPREME

15W40 – 20W50 SM/CF-4 (Code: 1503, 1003)



DEFINITION

ULTRATEC SUPREME 15W40 & 20W50 is a multi grade engine oil that provides superior engine protection suitable for today's multi-valve and conventional engines. Incorporating the latest additive technology, designed for today's conditions, It provides optimum protection against sludge formation, higher temperatures and helps keep the engine clean and free of deposits under high speed high stress motoring conditions.

ULTRATEC SUPREME 15W40 & 20W50 provides good wear protection at low temperatures combining easy low temperature engine start up and fast oil circulation at cold start up when the engine is at its most critical.

ULTRATEC SUPREME 15W40 & 20W50 meets or exceeds the following specifications.

- * API SM/CF
- * JASO VTW
- * CCMC G4, D4, PD-2
- * DAIMLER BENZ DB 229.1
- * VW 501.01 and 505.00
- * FORD ESE-M2C153E
- * ACEA A3, B3

APPLICATIONS

ULTRATEC SUPREME 15W40 & 20W50 is formulated for most types of passenger, 4WD, and light commercial vehicle engines covering Petrol, Diesel and LPG naturally aspirated or turbo charged.

ULTRATEC SUPREME 15W40 & 20W50 meets or exceeds the requirements of an SM/CF-4 engine oil. It has a highly effective detergent and dispersant system to keep engine internals clean.

It provides a high level of protection against wear and assists in energy conservation and fuel economy.

TYPICAL MAIN CHARACTERISTICS

	15W40	20W50
Specific gravity at 15c	0.882	0.889
Kinematic viscosity at 40 C, mm ² /s (cSt)	112	170
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.5	19
Viscosity index 142	142	127
Phosphorous maximum %	0.90	1.15
TBN, mgKOH/g	9.1	9.1

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd
Website www.ultralube.com.au

Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances.

All Packages should be stored under cover to avoid water contamination and fading. Do not store products over 60°C

PACKAGE SIZE Bulk, 205 Litre, 20 Litre, 5 Litre.

ULTRA LUBRICANTS