

XHD SILVER

15W40 CH-4/SJ (Code: 2001)



DEFINITION

XHD Silver 15W40 CH4 is a heavy duty multigrade diesel engine oil designed for use in high speed, four stroke diesel engines meeting the requirements of American, European and Japanese engine manufactures.

XHD Silver 15W40 CH4 meets or exceeds the following specifications.

- * API CH-4/SJ
- * VOLVO VDS-2
- * ACEA A3, B3, E2
- * MTU Type 2
- * US MILITARY - MIL-L-2104E, MIL-L- 46152E.
- * GENERAL MOTORS 6048M, 6G49M, 6085M.
- * MACK EO-M, EO-M PLUS
- * CUMMINS CES 20076, 20071
- * FORD ESE-M2C-1 53E, E8N-M2C-1 21 B
- * ALLISON Type C-4 (SAE 30)
- * DETROIT DIESEL Series 40, 50, 55, 60 engines
- * CATERPILLAR TO-2

APPLICATIONS

XHD SILVER 15W40 CH4 is designed to meet 1998 emission standards, It has been formulated for heavy duty service in engines specifically designed for on and off highway conditions.

TYPICAL MAIN CHARACTERISTICS

Specific gravity at 15c	0.885
Kinematic viscosity at 40 C, mm ² /s (cSt)	115
Kinematic viscosity at 100 C, mm ² /s (cSt)	14.7
Viscosity index	139
Sulfated ash %	1.2%
TBN, mgKOH/g	8.9

Materials Safety Data Sheet for this product can be obtained by visiting Ultra Lubricants International Pty. Ltd
Website www.ultralube.com.au

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C. Due to continual product research and development, the information contained herein is subject to formulation change without notice. Values stated are average values only and may vary due to manufacturing tolerances

PACKAGE SIZE Bulk, 205 Litre, 20 Litre, 5 Litre.

ULTRA LUBRICANTS

23 Tempest Street, Gunnedah NSW 2380 PH: 61 2 6742 5333 EMAIL: sales@ultralube.com.au www.ultralube.com.au